



# DİM-KA®

## HALAT

### ÖRGÜLÜ HALAT (POLYAMİD)

Kod. No:	ÇAP mm.	KOPMA GÜCÜ Kg./daN	AĞIRLIK gr/m
K1202	2	120	3
K1203	3	250	6,5
K1204	4	315	10,5
K1205	5	510	15,6
K1206	6	670	22,4
K1208	8	1190	39,8
K1210	10	1855	62,0
K1212	12	2660	89,6
K1214	14	3610	122
K1216	16	4700	159
K1218	18	5945	202
K1220	20	7320	249
K1224	24	10505	358
K1228	28	14280	488
K1232	32	18665	637
K1136	36	23560	806



Malzeme	İç Yapı	Yüksek Mukavemetli Teknolojik Polyamid
	Dış Kılıf	Yüksek Mukavemetli Teknolojik Polyamid
Halat Yapısı	Dış Kılıf: 16-24-32 Kollu, İç Yapı: 12-16 Kollu	
Özellikleri	Yüksek Mukavemet ve uzama, Kolay Kasa Yapımı, Elle Kolay Tutuş, Yüksek Dayanıklılık, Çok İyi Sürtünme Dayanımı	
Standartlar	TS EN 14685	

Material	Core	High Tenacity Multiflament Polyamide Fibres
	Cover	High Tenacity Multiflament Polyamide Fibres
Construction	Cover: 16-24-32 Plaited, Core: 12-16 Plaited	
Properties	Excellent Breaking Load & Elongation, Very Easily Spliced, Excellent Durability, Very Resistant to Abrasion, Easy Handling	
Standards	TS EN 14685	

